



TECHNICAL DATASHEET

PRODUCT NAME – RUST-X RP oil

PRODUCT CODE – VCI 135 Dry

PRODUCT DESCRIPTION

RUSTX oils contain VCI chemicals, which work in contact phase as well as in the vapor phase and protect components by its dual action. RUSTX – 135 Dry EX is a light grade of rust preventive oil, which provides a dry rust preventive coating on the parts.

RUSTX – 135 Dry is a **very thin grade or almost invisible dry to touch grade** of rust preventive oil, which provides a dry rust preventive coating on the parts and is suitable where frictional requirements have to be met. This also produces negligible fumes on **welding**. Hence it is most suitable to be used on areas that have to be welded and doesn't release fumes upon welding.

It is highly **dewatering in nature** and removes any contaminants like cutting oil and washing fluids on the parts.

The VCI fraction evaporates and reaches hard to reach surfaces where the direct oil spray cannot reach and protects the equipment from corrosion.

All RUST-X rust preventive oils are Barium & Heavy Metal Free.

FEATURES

- Feel dry to touch
- Good coverage due to low viscosity- high floatability & high penetration properties
- Less consumption due to thin film
- Long Term Corrosion Prevention
- Allow 2-10 minutes drain and drying time depending upon product requirement
- Excellent protection against acidic & saline environments
- Does not produce fumes during welding or heat treatment
- Non Sticky washable film
- Paintable in paint line

APPLICATIONS

- Machined Steel Components
- Castings
- Forgings
- CR sheets
- Bearings, Gears
- Transmission Components
- Axles, Process Equipment
- Flanges
- Valves etc.

PACKAGING AND STORAGE

Store in a cool dry place and always keep RPO sealed when not in use.



TECHNICAL DATASHEET

PRODUCT NAME – RUST-X RP oil

PRODUCT CODE – VCI 135 Dry

TECHNICAL SPECIFICATION

Physical Properties	Test Method	Value
Color	Visual	Amber Clear
Viscosity @ cSt @ 40°C	ASTM D 445	2~3 cSt
Specific Gravity	ASTM D 1298	0.78 - 0.86
Flash Point (before application)	ASTM D 92	<100 °C
Flash Point (after application)	ASTM D 92	<220 °C
Volatiles by % (by weight)		90 %
Coverage (sq m/ Lt)		100
Film thickness	IS 2074	0.75-1 Microns
Pour Point	ASTM D 97	Below -5°C
Saponification Value (mg KOH/gm)	ASTM D 94	5.0-7.0
Salt Spray Protection	ASTM B 117	24 hours +
Salt Spray in VCI Packaging	ASTM B 117	720 hours +
Humidity Chamber	ASTM D 1748	500 hours +
Indoor Protection Life (open)		2-3 months
Indoor protection life (packed)		2 years
Packaged Protection Life (In VCI Packaging)		Up to 5 Years

DISPOSAL

Recommendation: Do not allow product to reach sewage system.

Disposal of product or waste must comply with official local regulations.

Packaging that cannot be recycled must be disposed in the same manner as the product.

APPLICATION PICTURES



HEAVY METALS DECLARATION

RUST-X Rust Preventive products do not contain Lead



TECHNICAL DATASHEET

PRODUCT NAME – RUST-X RP oil

PRODUCT CODE – VCI 135 Dry

(Pb), Mercury (Hg), Cadmium (Cd), Hexavalent Chromium (Cr6), Polybrominated biphenyls (PBB), or Polybrominated di-phenylether complying with the restricted substances listed in Article 4(1) of the RoHS Directive. RUST-X Rust Preventive Oils are also REACH Compliant for exports to the European Union.

SAFETY INFORMATION

- Keep Out Of Reach Of Children
- Keep Container Tightly Closed
- Not For Internal Consumption
- Consult Material Safety Data Sheet For More Information
- Safe for people
- This product does not pose a health hazard to users due to its classification as an article according to EU REACH, UN GHS, US OSHA HazCom and CA WHMIS regulations.
- Rust-X VCI chemistry is safe for sensitive electronics.
- Rust-X VCI chemistry imposes No galvanic effects, residues or changes in the properties of metals. The protective molecules dissipate upon opening of package.

DECLARATION

This Data sheet and information it contains is considered to be accurate at the date of printing. No representation or warranty, expressed or implied is made as to the accuracy or completeness of the data

and information contained in this publication. It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations.

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on validations and tests conducted by HI TECH INTERNATIONAL/RUST-X or its partners and are believed to be reliable, but the accuracy or completeness thereof is not guaranteed. We warrant our products will be free from defects when shipped to customer. Our obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Rust-X, Hi Tech International or its partners or agent of the claimed defect within 3 months after shipment of product to customer. Customer shall pay all freight charges for replacement products. We shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products. And any financial claims shall be limited to the value of the film sold.

Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. No representation or recommendation not contained herein shall have any force or effect unless in a written



TECHNICAL DATASHEET

PRODUCT NAME – RUST-X RP oil

PRODUCT CODE – VCI 135 Dry

document signed by an officer of the company. The foregoing warranty is exclusive and in lieu of all other warranties, express, implied or statutory, including without limitation any implied warranty of merchantability or of fitness for a particular purpose. In no case shall HI TECH INTERNATIONAL/RUST-X be liable for incidental or consequential damages.

GLOBAL SUPPORT

Algeria Angola Argentina Australia Austria Bangladesh Belarus Belgium Bhutan Bolivia Brazil Canada Chile China Colombia Czech Republic Democratic Republic of the Congo Denmark Ecuador Estonia Finland France Gabon Germany Hungary India Indonesia Ireland Italy Japan Kazakhstan Korea Latvia Lithuania Luxembourg Malaysia Mexico Monaco Morocco Nepal Netherlands Nigeria Norway Peru Philippines Poland Portugal Republic of Congo Romania Russia Singapore Slovak Republic Slovenia South Africa Spain Sri Lanka Sweden Switzerland Taiwan Thailand Tunisia Turkey Ukraine United Arab Emirates and MENA (Middle East & North Africa) United Kingdom United States Uruguay Vietnam



DISTRIBUTED BY -

FOR INDUSTRIAL USE ONLY
Revision No. 2 Revision Date: 1st March 2019